



58BW/BD WINDOW AND DOOR SYSTEM

The 58BW/BD window and door system is the perfect choice for residential or commercial projects, offering a cost effective, high performance solution in a wide range of configurations and formats to suit your building design. The window system is available in Top Hung, Side Hung, Tilt before Turn, Fully Reversible and Steel Replacement formats with a range of glazing and hardware options. With clean lines and advanced functionality, this superior window and door system offers you the choice and flexibility to meet your needs.

DESIGN FEATURES

- Windows available in internally or externally glazed options
- Flat, chamfered or Ovolo details to achieve traditional or contemporary appearances
- 58mm or 70mm frame depth to accommodate varying types of applications
- Project in or project out options, where applicable
- Integrated deep head profiles for ease of trickle ventilation
- Unique polyamide thermal break design to improve thermal performance
- Certified under Secured by Design scheme
- Door system with unique Polyamide Euro groove design
- Sculptured detail that creates a picture frame view through the door
- Accepts a full range of restrictors and access control devices
- Available as a standard door option or with PAS 23 / PAS24 upgrade
- Multi-point locking mechanisms for enhanced security
- Cloaking feature conceals lock and prevents any access to locking points

OPTIONS

- Accommodates 24mm - 44mm glazing units for thermal and acoustic performance
- Double beaded option allow for internal glazing without the use of dummy vents
- Dedicated fixing straps for ease of installation
- Low threshold door option to comply with Part M – Building Regulation
- Full range of customisable hardware available
- Available in single or dual colour option, polyester powder coating and anodised finishes

WINDOW CONFIGURATIONS

- Top Hung and Side Hung
- Side Hung & Bottom Hung (Open In)
- Tilt/Turn & Turn/Tilt
- Tilt & Slide
- Fully reversible
- Internally glazed beading options
- Project in or project out options
- Lifetime Homes (LTH)

DOOR CONFIGURATIONS

- Single Doors (Open In)
- Single Doors (Open Out)
- Double Doors (Open In)
- Double Doors (Open Out)
- Lifetime Homes (LTH)




58BW/BD WINDOW AND DOOR SYSTEM TECHNICAL SPECIFICATIONS

The 58BW/BD window and door system has been designed to offer a high performance, narrow profile solution that has the range and flexibility to suit most projects. Windows are available in Top Hung, Side Hung, Tilt Before Turn and Fully-Reversible formats and a complete range of colours and finishes. Anodised finishes

are also available with marine grade guarantees on request. Certified under the Secured by Design scheme, and meeting all relevant standards, this competitively priced window and door system offers complete choice and flexibility.

SPECIFICATIONS	OUTWARD OPENING	INWARD OPENING	FULLY REVERSIBLE	SINGLE & DOUBLE DOOR
Performance & Accreditation				
U-Value (Double Glazing)*	1.4 W/m²K	1.6 W/m²K	1.7 W/m²K	1.7 W/m²K
U-Value (Triple Glazing)**	1.2 W/m²K	1.2 W/m²K	--	1.4 W/m²K
Window Energy Rating (WER)	B - C	B - C	npd	npd
Green Guide Rating	A+ - A Rated	A+ - A Rated	B Rated	npd
Acoustic Performance (dB)	Rw (C;Ctr) 42 (-1;-5) dB	Rw (C;Ctr) 42 (-1;-5) dB	npd	npd
Air Tightness (Pa)	Class 4	Class 3	Class 4	Class 4
Water Tightness (Pa)	Class 9a	Class 9a	Class 6a	Class 7a
Wind Load (Pa)	Class E2400	Class E2400	Class 5	Class E2400
Security	Kitemarked to PAS 24	Kitemarked to PAS 24	Kitemarked to PAS 24	Kitemarked to PAS 24
Secured By Design	Yes	Yes	Yes	Yes
Configurations				
Opening	Open Out	Open In	Open Out	Open In & Open Out
Top Hung	●	--	--	--
Side Hung	●	--	--	--
Bottom Hung	●	--	--	--
Fixed Light	●	●	●	●
Multilight	●	--	--	--
Tilt & Turn	--	●	--	--
Life Time Homes (LTH)	--	●	--	--
Tilt & Slide	--	●	--	--
Top swing	--	--	●	--
Side Swing	--	--	●	--
Size Limits				
Max Vent Weight	--	--	--	90 Kg
Top Hung	90 Kg	--	--	--
Side Hung	55 Kg	--	--	--
Bottom Hung	60 Kg (3 Hinges)	100 Kg	--	--
Fixed Light	250 Kg	--	--	--
Tilt & Turn	--	100 Kg	--	--
Life Time Homes (LTH)	--	100 Kg	--	--
Tilt & Slide	--	100 Kg	--	--
Top swing	--	--	60 Kg	--
Side Swing	--	--	50 Kg	--
System Features				
Frame Options	58mm & 70mm	58mm & 70mm	70mm	58mm & 70mm
Dual Colour Option	●	●	●	●
Multi-Point Locking	●	●	●	●
Glazing Options	Internal & External	Internal	Internal	Internal
Glazing Thickness	24mm - 44mm	24mm - 44mm	28mm	24mm - 44mm

CAD CROSS SECTIONS AND THERMAL PROFILE



* Window Energy Ratings and U-Values based on CEN size windows (1230mm x 1480mm) using 1.2 W/m²K double glazing with warm edge Swisspacer V bar. ** U-Values based on CEN size windows (1230mm x 1480mm) using 0.7 W/m²K triple glazing with warm edge Swisspacer V bar. Corresponds to the BRE Global Green Guide online generic specification for domestic windows and achieves a summary rating of B-C. www.thegreenguide.org.uk Element Number 813100001/813100007. * Door U-Values based on CEN size ≤ 3600mm² using 1.2 W/m²K double glazing with warm edge Swisspacer V bar. ** U-Values based on CEN size ≤ 3600mm² using 0.7 W/m²K triple glazing with warm edge Swisspacer V bar. All weather test data taken from BS EN 6375-1 (Part of Pas 23) based upon highest performing door configuration. Sound insulation values are Rw reduction values and are based on tests using acoustic glazing.

Please note: NBS Specifications are available for all products and BIM Components for many. Please visit www.aluk.co.uk to download CAD files, BIM Components and NBS Specifications.